

4096 BIT DYNAMIC RAMS**3****DESCRIPTION**


The μPD411A Family consists of four 4096 words by 1 bit dynamic N-channel MOS RAMs. They are designed for memory applications where very low cost and large bit storage are important design objectives. The μPD411A Family is designed using dynamic circuitry which reduces the standby power dissipation.

Reading information from the memory is non-destructive. Refreshing is easily accomplished by performing one read cycle on each of the 64 row addresses. Each row address must be refreshed every two milliseconds. The memory is refreshed whether Chip Select is a logic high or a logic low.

FEATURES

- Low Standby Power
- 4096 words x 1 bit Organization
- A single low-capacitance high level clock input with solid ± 1 volt margins.
- Inactive Power 0.7 mW (Typ.)
- Power Supply +12, +5, -5V
- Easy System Interface
- TTL Compatible (Except CE)
- Address Registers on the Chip
- Simple Memory Expansion by Chip Select
- Three State Output and TTL Compatible
- 22 pin Plastic Dual-in-Line Package
- Replacement for INTEL's 2107B, TI's 4060 and Equivalent Devices.
- 3 Performance Ranges:

	ACCESS TIME	R/W CYCLE	RMW CYCLE	REFRESH TIME
μPD411A	300 ns	470 ns	650 ns	2 ms
μPD411A-1	250 ns	430 ns	600 ns	2 ms
μPD411A-2	200 ns	400 ns	520 ns	2 ms

PIN CONFIGURATION**PIN NAMES**

A ₀ - A ₁₁	Address Inputs
A ₀ - A ₅	Refresh Addresses
CE	Chip Enable
CS	Chip Select
DIN	Data Input
DOUT	Data Output
WE	Write Enable
VDD	Power (+12V)
VCC	Power (+5V)
VSS	Ground
VBB	(Power, -5V)
NC	No Connection

μPD411A

CE Chip Enable

A single external clock input is required. All read, write, refresh and read-modify-write operations take place when chip enable input is high. When the chip enable is low, the memory is in the low power standby mode. No read/write operations can take place because the chip is automatically precharging.

FUNCTIONAL DESCRIPTION

CS Chip Select

The chip select terminal affects the data in, data out and read/write inputs. The data input and data output terminals are enabled when chip select is low. The chip select input must be low on or before the rising edge of the chip enable and can be driven from standard TTL circuits. A register for the chip select input is provided on the chip to reduce overhead and simplify system design.

WE Write Enable

The read or write mode is selected through the write enable input. A logic high on the WE input selects the read mode and a logic low selects the write mode. The WE terminal can be driven from standard TTL circuits. The data input is disabled when the read mode is selected.

A0–A11 Addresses

All addresses must be stable on or before the rising edge of the chip enable pulse. All address inputs can be driven from standard TTL circuits. Address registers are provided on the chip to reduce overhead and simplify system design.

DIN Data Input

Data is written during a write or read-modify-write cycle while the chip enable is high. The data in terminal can be driven from standard TTL circuits. There is no register on the data in terminal.

DOUT Data Output


The three state output buffer provides direct TTL compatibility with a fan-out of two TTL gates. The output is in the high-impedance (floating) state when the chip enable is low or when the Chip Select input is high. Data output is inverted from data in.

Refresh

Refresh must be performed every two milliseconds by cycling through the 64 addresses of the lower-order-address inputs A₀ through A₅ or by addressing every row within any 2-millisecond period. Addressing any row refreshes all 64 bits in that row.

The chip does not need to be selected during the refresh. If the chip is refreshed during a write mode, the chip select must be high.

BLOCK DIAGRAM



ABSOLUTE MAXIMUM RATINGS*

Operating Temperature	0°C to +70°C
Storage Temperature	-55°C to +125°C
Output Voltage ①	+20 to -0.3 Volts
All Input Voltages ①	+20 to -0.3 Volts
Supply Voltage V _{DD} ①	+20 to -0.3 Volts
Supply Voltage V _{CC} ①	+20 to -0.3 Volts
Supply Voltage V _{SS} ①	+20 to -0.3 Volts
Power Dissipation	1.0W

Note: ① Relative to V_{BB}.

COMMENT: Stress above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

*T_a = 25°C

DC CHARACTERISTICS

PARAMETER	SYMBOL	LIMITS			UNIT	TEST CONDITIONS
		MIN.	TYP. ①	MAX.		
Input Load Current	I _{LI}		0.01	10	μA	V _{IN} = V _{IL MIN} to V _{IH MAX}
CE Input Load Current	I _{LC}		0.01	10	μA	V _{IN} = V _{ILC MIN} to V _{IH MAX}
Output Leakage Current for High Impedance State	I _{LO}		0.01	±10	μA	CE = V _{ILC} or CS = VIH V ₀ = 0V to 5.25V
V _{DD} Supply Current during CE off	I _{DD OFF}		50	200	μA	CE = -1.0V to 0.6V
V _{DD} Supply Current during CE on	I _{DD ON}		35	50	mA	CE = V _{IH C} , T _a = 25°C
Average V _{DD} Current μPD411A μPD411A-1 μPD411A-2	I _{DD AV}		38 38 38	55 55 55	mA	T _a = 25°C Cycle Time = 470 ns Cycle Time = 430 ns Cycle Time = 400 ns
V _{BB} Supply Current ②	I _{BB}		5	100	μA	
V _{CC} Supply Current during CE off ③	I _{CC OFF}		0.01	10	μA	CE = V _{ILC} or CS = VIH
Input Low Voltage	V _{IL}	-1.0		0.6	V	
Input High Voltage	V _{IH}	2.4		V _{CC} + 1	V	
CE Input Low Voltage	V _{ILC}	-1.0		0.6	V	
CE Input High Voltage	V _{IHC}	V _{DD} - 1	V _{DD}	V _{DD} + 1	V	
Output Low Voltage	V _{OL}	0		0.40	V	I _{OL} = 3.2 mA
Output High Voltage	V _{OH}	2.4		V _{CC}	V	I _{OH} = -2.0 mA

Notes: ① Typical values are for T_a = 25°C and nominal power supply voltages.

② The I_{BB} current is the sum of all leakage currents.

③ During CE on V_{CC} supply current is dependent on output loading.

CAPACITANCE

T_a = 0°C to 70°C, V_{DD} = 12V ± 10%, V_{CC} = +5V ± 10%, V_{BB} = -5V ± 10%, V_{SS} = 0V

PARAMETER	SYMBOL	LIMITS			UNIT	TEST CONDITIONS
		MIN.	TYP.	MAX.		
Address Capacitance	C _{AD}			6	pf	V _{IN} = V _{SS}
CS Capacitance	C _{CS}			6	pf	V _{IN} = V _{SS}
DIN Capacitance	C _{IN}			6	pf	V _{IN} = V _{SS}
D _{OUT} Capacitance	C _{OUT}			7	pf	V _{OUT} = V _{SS}
WE Capacitance	C _{WE}			7	pf	V _{IN} = V _{SS}
CE Capacitance	C _{CCE1}			27	pf	V _{IN} = V _{SS}
	C _{CCE2}			22	pf	V _{IN} = V _{DD}

μ PD411A

AC CHARACTERISTICS

READ CYCLE

$T_a = 0^\circ C$ to $70^\circ C$, $V_{DD} = 12V \pm 10\%$, $V_{CC} = 5V \pm 10\%$, $V_{BB} = 5V \pm 10\%$, $V_{SS} = 0V$, unless otherwise noted.

PARAMETER	SYMBOL	LIMITS						TEST CONDITIONS
		μ PD411A		μ PD411A-1		μ PD411A-2		
		MIN	MAX	MIN	MAX	MIN	MAX	UNIT
Time Between Refresh	t _{REF}		2		2		2	ms
Address to CE Set Up Time	t _{AC}	0		0		0		ns
Address Hold Time	t _{AH}	150		150		150		ns
CE Off Time	t _{CC}	130		130		130		ns
CE Transition Time	t _T	0	40	0	40	0	40	ns
CE Off to Output High Impedance State	t _{CF}	0	130	0	130	0	130	ns
Cycle Time	t _{CY}	470		430		400		ns
CE on Time	t _{CE}	300	3000	260	3000	230	3000	ns
CE Output Delay	t _{CO}		280		230		180	ns
Access Time	t _{ACC}		300		250		200	ns
CE to WE	t _{WL}	40		40		40		ns
WE to CE on	t _{WC}	0		0		0		ns

WRITE CYCLE

$T_a = 0^\circ C$ to $70^\circ C$, $V_{DD} = 12V \pm 10\%$, $V_{CC} = 5V \pm 10\%$, $V_{BB} = 5V \pm 10\%$, $V_{SS} = 0V$, unless otherwise noted.

PARAMETER	SYMBOL	LIMITS						TEST CONDITIONS
		μ PD411A		μ PD411A-1		μ PD411A-2		
		MIN	MAX	MIN	MAX	MIN	MAX	UNIT
Cycle Time	t _{CY}	470		430		400		ns
Time Between Refresh	t _{REF}		2		2		2	ms
Address to CE Set Up Time	t _{AC}	0		0		0		ns
Address Hold Time	t _{AH}	150		150		150		ns
CE Off Time	t _{CC}	130		130		130		ns
CE Transition Time	t _T	0	40	0	40	0	40	ns
CE Off to Output High Impedance State	t _{CF}	0	130	0	130	0	130	ns
CE on Time	t _{CE}	300	3000	260	3000	230	3000	ns
WE to CE off	t _W	180		180		150		ns
CE to WE	t _{CW}	300		260		230		ns
DIN to WE Set Up ①	t _{DW}	0		0		0		ns
DIN Hold Time	t _{DH}	40		40		40		ns
WE Pulse Width	t _{WP}	180		180		150		ns

Note. ① If WE is low before CE goes high then DIN must be valid when CE goes high.


READ-MODIFY-WRITE CYCLE

$T_a = 0^\circ C$ to $70^\circ C$, $V_{DD} = 12V \pm 10\%$, $V_{CC} = 5V \pm 10\%$, $V_{BB} = 5V \pm 10\%$, $V_{SS} = 0V$, unless otherwise noted.

PARAMETER	SYMBOL	LIMITS						TEST CONDITIONS
		μ PD411A		μ PD411A-1		μ PD411A-2		
		MIN	MAX	MIN	MAX	MIN	MAX	UNIT
Read-Modify-Write (RMW) Cycle Time	t _{RWC}	650		600		520		ns
Time Between Refresh	t _{REF}		2		2		2	ms
Address to CE Set Up Time	t _{AC}	0		0		0		ns
Address Hold Time	t _{AH}	150		150		150		ns
CE Off Time	t _{CC}	130		130		130		ns
CE Transition Time	t _T	0	40	0	40	0	40	ns
CE Off to Output High Impedance State	t _{CF}	0	130	0	130	0	130	ns
CE Width During RMW	t _{CRW}	480	3000	430	3000	350	3000	ns
WE to CE on	t _{WC}	0		0		0		ns
WE to CE off	t _W	180		180		150		ns
WE Pulse Width	t _{WP}	180		180		150		ns
DIN to WE Set Up	t _{DW}	0		0		0		ns
DIN Hold Time	t _{DH}	40		40		40		ns
CE to Output Delay	t _{CO}		280		230		180	ns
Access Time	t _{ACC}		300		250		200	ns


TIMING WAVEFORMS

READ AND REFRESH CYCLE ①




3

WRITE CYCLE




READ-MODIFY-WRITE CYCLE



- Notes:
- ① For refresh cycle, row and column addresses must be stable t_{AC} and remain stable for entire t_{AH} period.
 - ② V_{DD} ~ 2V is the reference level for measuring timing of CE.
 - ③ V_{SS} + 2V is the reference level for measuring timing of CE.
 - ④ V_{IHMN} is the reference level for measuring timing of the addresses, CS, WE and D_{IN}.
 - ⑤ V_{ILMAX} is the reference level for measuring timing of the addresses, CS, WE and D_{IN}.
 - ⑥ V_{SS} + 2.0V is the reference level for measuring timing of D_{OUT}.
 - ⑦ V_{SS} + 0.8V is the reference level for measuring timing of D_{OUT}.
 - ⑧ WE must be at V_{IH} until end of t_{CO}.

μ PD411A



TYPICAL OPERATING CHARACTERISTICS

$$\text{Power consumption} = V_{DD} \times I_{DDAV} + V_{BB} \times I_{BB}$$

POWER CONSUMPTION


Typical power dissipation for each product is shown below.

	mW (TYP.)	CONDITIONS
μ PD411A	460 mW	$T_a = 25^{\circ}\text{C}$, $t_{CY} = 470\text{ ns}$, $t_{CE} = 300\text{ ns}$
μ PD411A-1	460 mW	$T_a = 25^{\circ}\text{C}$, $t_{CY} = 430\text{ ns}$, $t_{CE} = 260\text{ ns}$
μ PD411A-2	460 mW	$T_a = 25^{\circ}\text{C}$, $t_{CY} = 400\text{ ns}$, $t_{CE} = 230\text{ ns}$

See curve above for power dissipation versus cycle time.

μ PD411A

CURRENT WAVEFORMS ①




3

25

■ 9004697 0113013 063 ■

μ PD411A

PACKAGE OUTLINE μ PD411AC



(PLASTIC)

ITEM	MILLIMETERS	INCHES
A	28.0 Max.	1.10 Max.
B	1.4 Max.	0.025 Max.
C	2.54	0.10
D	0.50	0.02
E	25.4	1.00
F	1.40	0.055
G	2.54 Min.	0.10 Min.
H	0.5 Min.	0.02 Min.
I	4.7 Max.	0.18 Max.
J	5.2 Max.	0.20 Max.
K	10.16	0.40
L	8.5	0.33
M	0.25 ^{+0.10} _{-0.05}	0.01 ^{+0.004} _{-0.002}